

## ERİŞİM TEKNİK OPTİK TURNİKELERİ

# 0-521

### KASA FRAME

304 Kalite Paslanmaz Çelik Gövde  
ve Cam Tabla  
304 Quality Stainless Steel Body and  
Glass Table

### GÖSTERGELER INDICATORS

Giriş ve Çıkış Tarafında İki Renkli  
Göstergeler Mevcuttur  
Two Color Indicators Available on  
Input and Output Sides

### KONTROL CONTROL

Kuru Kontak / Her Türlü Kartlı Geçiş  
Sistemi İle Çalışır  
Dry Contact / All Kinds of Access Control  
System

### GÜVENLİK SECURITY

28 adet Karşılıklı Fotosel, Sıkışma Anında  
Geri Gelebilmeye  
28 Photocells, Recovery When jamming

### KANAT WING


10mm Temper Cam  
10mm Temper Glass

### ACİL DURUM EMERGENCY

Enerji Kesildiğinde, Akü Desteksiz  
El İle Açılabilir  
When the Power is Cut, The Battery  
Can Be Opened Manually Without  
Support

ENERJİ 220V AC / FREKANS 50-60 HZ / MAKSİMUM GÜÇ 20 W DOUBLE TURNİKE 40 W / AKIM TÜRÜ VE DEĞERİ 2A DOUBLE TURNİKE 4.5A / IP 55 / GÜVENLİK SINIFI 1 / ÇALIŞMA SICAKLIĞI -20 +45 / ÇALIŞMA NEMİ %95 MAX.  
**GARANTİ SÜRESİ 2 YIL / KULLANIM SÜRESİ 10 YIL**

ENERGY 220V AC / FREQUENCY 50-60 HZ / MAXIMUM POWER 20 W DOUBLE TURNSTILE 40 W / CURRENT TYPE AND VALUE 2A DOUBLE TURNSTILE 4.5A / IP 55 / SAFETY CLASS 1 / OPERATING TEMPERATURE -20 +45  
OPERATING HUMIDITY 95% MAX. **WARRANTY PERIOD 2 YEARS / USAGE PERIOD 10 YEARS**



### UYGULANABİLİR ÖZELLİKLER / APPLICABLE FEATURES



Kanatlara  
Logo  
Special Design and  
Production



Üst Kapak Mermere  
veya Pleksiglass  
External Audible  
Warning



IP 65'e Kadar  
Uygulanabilir  
Koruma Sınıfı  
Applicable  
Protection Class up  
to IP 65